

MG-Series

Multi Purpose Grab for **NOX** Tiltrotators

Especially adapted to our **NOX** Tiltrotators, this multi purpose grab is ideal for excavator with 9t up to 22t operating weight.

- Flexible multi purpose grab for difficult and heavy tasks.
- Counter-balance valve and pressure reservoir for maximum safety.
- Extra strong hydraulic cylinder
- Conical pin design to avoid clearance in the joint.
- SuperSaw 555S mountable saw available for all models.



MG16-S60

Multi Purpose Grab with hydraulic cylinder

Type	for NOX	Width E (mm)	Opening A (mm)	Volume (m ³)	Load capacity (kg)	Closing force** (kN)	Operating weight (t)
MG12	TR14NOX	454	1496	0,26	6000	22	9 - 14
MG16	TR19NOX	531	1822	0,36	8000	27	12 - 18
MG20	TR25NOX	531	2279	0,52	10000	33	16 - 22

Package consists of: multi purpose grab, adapter *

** at 35 MPa

* standard adapters see table - other adapters available on request

Adapters

Type grab	Type adapter
MG12	S45
MG12	S50
MG12	S60
MG12	OQ45
MG12	OQ60
MG16	S50
MG16	S60
MG16	S70
MG16	OQ60
MG16	OQ60-5
MG16	OQ70
MG20	S60
MG20	S70
MG20	OQ70



MG16-S60

Requirements of Excavator

	MG12	MG16	MG20
Operating pressure:	max. 35 MPa (350 bar)	max. 35 MPa (350 bar)	max. 35 MPa (350 bar)

Technical Drawings

MG16-S60

