

Fork Tines for **NOX**-Tiltrotators 3-12t / 6,600-26,400lbs

GAF / GAH

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ High load capacity.
- ▷ Low self-weight.
- ▷ Very economic: low cost.
- ▷ Ideal for use with Tiltrotator: highest flexibility.
- ▷ Two versions available: with mechanically or hydraulically adjustable tines.
- ▷ Easy mounting thanks to a quick change adapter.
- ▷ Different adapters available.



## Mechanic Fork Tines GAF

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
<b>GAF6</b>	TR045NOX / TR07NOX	S40	1,900 / 4,180	1,000 / 39.3	140 / 308	1,000 / 39.3	3 - 6 / 6,600 - 13,200
<b>GAF8</b>	TR07NOX / TR11NOX	S45	1,900 / 4,180	1,200 / 47.2	190 / 418	1,000 / 39.3	6 - 8 / 13,200 - 17,600
<b>GAF12</b>	TR11NOX	S45	2,500 / 5,500	1,200 / 47.2	200 / 440	1,200 / 47.2	9 - 12 / 19,800 - 26,400

**Package consists of:** fork tines, frame with standard suspension for S-couplers\*

## Hydraulic Fork Tines GAH

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
<b>GAH6</b>	TR045NOX / TR07NOX	S40	1,900 / 4,180	1,000 / 39.3	160 / 352	1,000 / 39.3	3 - 6 / 6,600 - 13,200
<b>GAH8</b>	TR07NOX / TR11NOX	S45	1,900 / 4,180	1,200 / 47.2	210 / 462	1,000 / 39.3	6 - 8 / 13,200 - 17,600
<b>GAH12</b>	TR11NOX	S45	2,500 / 5,500	1,200 / 47.2	220 / 484	1,200 / 47.2	9 - 12 / 19,800 - 26,400

**Package consists of:** hydraulic fork tines, frame with standard suspension for S-couplers\*

\*other adapters available on request

**Note:** put loads always the nearest to the back and to the centre of gravity

## Requirements for carrier machine



The excavator must be conform to lifting regulations

## Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter



Hydraulically adjustable fork tines here with cylinderless **NOX** Tiltrotator

Request? [exc@kinshofer.com](mailto:exc@kinshofer.com)

Fork Tines for **NOX**-Tiltrotators 13-24t / 28,600-52,800lbs

GAF / GAH

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF or GAH Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ High load capacity.
- ▷ Low self-weight.
- ▷ Very economic: low cost.
- ▷ Ideal for use with Tiltrotator: highest flexibility.
- ▷ Two versions available: with mechanically or hydraulically adjustable tines.
- ▷ Easy mounting thanks to a quick change adapter.
- ▷ Different adapters available.



## Mechanic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
<b>GAF18</b>	TR14NOX TR19NOX	S45 S60	4,000 / 8,800	1,200 / 47.2	340 / 748	1,200 / 47.2	13 - 18 / 28,600 - 39,600
<b>GAF20</b>	TR19NOX TR25NOX	S70	4,000 / 8,800	1,200 / 47.2	420 / 924	1,200 / 47.2	19 - 20 / 41,800 - 44,000
<b>GAF24</b>	TR25NOX	S70	5,000 / 11,000	1,200 / 47.2	440 / 968	1,200 / 47.2	21 - 24 / 46,200 - 52,800

**Package consists of:** fork tines, frame with standard suspension for S-couplers\*

## Hydraulic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
<b>GAH18</b>	TR14NOX TR19NOX	S45 S60	4,000 / 8,800	1,200 / 47.2	340 / 748	1,200 / 47.2	13 - 18 / 28,600 - 39,600
<b>GAH20</b>	TR19NOX TR25NOX	S70	4,000 / 8,800	1,200 / 47.2	420 / 924	1,200 / 47.2	19 - 20 / 41,800 - 44,000
<b>GAH24</b>	TR25NOX	S70	5,000 / 11,000	1,200 / 47.2	440 / 968	1,200 / 47.2	21 - 24 / 46,200 - 52,800

**Package consists of:** hydraulic fork tines, frame with standard suspension for S-couplers\*

\*other adapters available on request

**Note:** put loads always the nearest to the back and to the centre of gravity

## Requirements for carrier machine



The excavator must conform to lifting regulations

## Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter



Hydraulically adjustable fork tines here with cylinderless **NOX** Tiltrotator

Request? [exc@kinshofer.com](mailto:exc@kinshofer.com)